



Step 1

Obtain the red Salvo Gladhand (SGL) with the key code pertaining to the correct loading dock number.

Note: The key code on the gladhand needs to match the Salvo Manual Door Lock.



Step 2

Remove the **RED** air line from semi trailer.



Step 3

Apply the gladhand by vertically inserting the head of the SGL into the coupling. Push forward and squeeze the two buttons on the sleeve to remove the key from the gladhand to engage.



Step 4

While pushing the SGL towards the coupling and pressing the buttons on the sleeve, turn the key counter-clockwise to remove the key from the gladhand.



Step 5

Insert the key in the Salvo Manual Door Lock, located on the interior of the dock door, and turn clockwise. Bolt can now be turned and removed from lock.



Step 6

Loading/unloading can take place.
Note: While the door is open the optional traffic light will remain red on the exterior of the building and the key will be trapped in the door lock.



Step 7

When loading/ unloading is complete, close the dock door, re-insert bolt into the Salvo Manual Door Lock and turn. The key can now be turned counter-clockwise and removed.



Step 8

Once the key is removed, drivers are made aware (with optional outside traffic light) that loading/unloading is complete.



Step 9

Insert the key into the gladhand and turn the key clockwise to remove the gladhand from the coupling.



Step 10

Return the gladhand to its original place and depart from the dock.