

# MOUNTING BOLTS & TOOLS



Part of the  
Sentric Group

## DESCRIPTION

**Tamperproof mounting bolts** are made from Stainless Steel. A tamperproof key tool or tamperproof bit tool is required to install the tamperproof mounting bolts and must be ordered separately.

Standard tamperproof mounting bolt lengths:

- a.) 3/8"-16 x 3/4" (for Type B and unhoued SKRU)
- b.) 3/8"-16 x 1-3/4" (for Type F, T, D and DM)
- c.) 3/8"-16 x 2-1/4" (for Type D Latch Block & Type U lock)
- d.) 1/4"-20 x 3/4" (for Type FN & PPS)
- e.) 1/4"-20 x 2" (for Type NT)
- f.) 1/4"-20 x 1-1/2" (for Type FF)

## ORDER INFORMATION



TAMPERPROOF

To order with interlock: place the letter "T" in the appropriate column of the interlock part number.

To order separately: reference the bolt length desired with BU following the bolt length indicating 'Tamperproof'.



TAMPERPROOFTOOLS

To order these tools with your tamperproof mounting bolts, please order by the specific part number listed below.

Part number 3/8" Bolt Key

2	1	H	K	H	K	A
---	---	---	---	---	---	---

Part number 1/4" Bolt Key

1	5	H	K	H	K	A
---	---	---	---	---	---	---

Part number 3/8" Bolt Bit

2	1	H	K	H	B
---	---	---	---	---	---

Part number 1/4" Bolt Bit

1	5	H	K	H	B
---	---	---	---	---	---

## CONTACT INFORMATION

### The Kirk Key Interlock Company LLC

9048 Meridian Circle, NW North Canton, OH 44720, USA

Toll Free: +1 800-438-2442 | O: +1 234-209-9301 | F: +1 330-497-4400

Quotes & Inquiries: sales@kirkkey.com | PO Submission & Orders: orders@kirkkey.com